

Model	SI-1L
Lamp:	LED Module : 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K. CRI = 85
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass, flush lens
Mounting:	4/0 or 3/0 junction covers
Stem Length:	12", 18", 24", 30", 36", 42", 48"
Socket:	GY 6.35 Bi-Pin Porcelain
Certification:	Wet location, IP Rating = 66
Wiring:	2 ft. 16/2 low voltage cable
Weight:	2.4 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 5" (fixture)



Shown in Bronze Powder Coat Finish (BZ)



2W/4W/6W/9W




METALS:

6061-T6 Aluminum



Mounting Options:



4/0 Round



4/0 Square



3/0 Round



4/0 Box

ORDERING LOGIC:

Model: SI - 1L

Metal: A - Aluminum

Mounting Plate: 1 - 4/0 round 2 - 4/0 square
3 - 3/0 round 4 - 4/0 box

Stem Length: 12 - 12" 36 - 36"
18 - 18" 42 - 42"
24 - 24" 48 - 48"
30" - 30"

Finish: BK - Black BKT - Black Texture
BZ - Bronze BZT - Bronze Texture
WT - White SL - Silver
BG - Beige CA - Clear Anodized

ORDERING EXAMPLE: SI - 1L - A - 1 - 24 - BK - 52*

*See page 2 to select module type to be installed

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.




4/0 BOX:

Made for surface mount applications. Fits on to a standard 4/0 junction box. It holds a TR-8 power supply for low voltage fixtures. Accepts standard 4/0 round junction box cover.



9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 12VAC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



45°



30°



60°

