
Specification-grade landscape lighting, wet-location luminaire for path or garden lighting applications.

- · Machined aluminum, available in seven standard TGIC powder coat finishes and clear anodized finish.
- · Machined brass or copper, available in two finishes.
- · Remote transformer required.
- · Stainless steel hardware.
- 6 feet of 18/2 low voltage cable supplied.
- · Shade diameter of 6 1/6".
- Stems lengths of 6" 36" available. Mount not included.
- Frosted or clear tempered glass lens, glued in.
- · High-temperature silicone O-ring seals are used to seal the cap against the body.
- Molded silicone wire pass-thru is attached to socket wire prevents wicking and water leaking into the lamp compartment.
- · Listed for wet location use.
- · Warranty: 10 Years.







MATERIAL:





Specifications

MODEL: PL-3

Machined Aluminum, Brass or Copper

VOLTAGE: 12V

WATTAGE: 35 Watt

SOCKET: GY-6.35 Bi-pin porcelain socket rated 600V,

250°C 18 ga, Teflon® coated leads.

LAMPING: T4 Halogen,

35W Maximum (order separately) 5W LED (order separately)

Ordering Logic:

MODEL METAL LENS STYLE SHADE TOP STEM LENGTH **FINISH** PL - 3 BKT - Black Texture A - Aluminum F - Frosted S - Standard 6 - 6" 18 - 18" BK - Black BZT - Bronze Texture B - Brass C - Clear T - Tall 9 - 9" 24 - 24" BZ - Bronze C - Copper Shade D - Dome 12 - 12" 30 - 30" WT - White SL - Silver CA - Clear Anodized C - Cone BG - Beige 36 - 36 NT - Natural DB - Dark Bronze

ORDERING EXAMPLE: PL - 3 - A - F - D - 12 - BZT

Excelsior Lighting, Inc.

PROJECT

TYPE