

Model	IN-1
Lamp:	MR16 Halogen or LED
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Accessories:	Holds Three accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	67
Certification:	Wet location landscape, UL1838
Wiring:	6' 16/2 Low Voltage Cable
Weight:	2.5 lbs.
Warranty:	Aluminum: 10 Years
Dimensions:	3" dia. x 5 3/8" overall (6" housing)



Shown in Bronze Powder Coat Finish (BZ)



SORAA

DAUER

BRILLIANCE



METALS:

6061-T6 Aluminum



Round Top



Square Top



FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model IN-1. Caps drain water even when aimed straight up.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.

ORDERING LOGIC:

Model:	IN - 1
Metal:	A - Aluminum
Top Style:	R - Round Top S - Square Top T - Tapered Top
Pour Collar:	0 - None (standard) PC - Pour Collar (optional)
Finish:	BK - Black BKT - Black Texture BZ - Bronze BZT - Bronze Texture WT - White SL - Silver BG - Beige CA - Clear Anodized



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

ORDERING EXAMPLE: IN - 1 - A - R - 0 - BK