
Specification-grade landscape lighting, wet-location luminaire for path, garden or wall wash lighting applications.

- · Extruded bronze and machined brass.
- · Available in Seven standard TGIC powder coat finishes and natural or dark bronze finishes.
- · Remote transformer required.
- · Stainless steel hardware.
- 6 feet of 18/2 low voltage cable supplied.
- · Available in heights of 9", 12" or 18".
- · Frosted tempered glass lens, glued in.
- 1/2" NPS mount threads (Mount not included.)
- · High-temperature silicone O-ring seals are used to seal the cap and body.
- · Listed for wet location use.
- · Warranty: 25 Years.









Specifications

MODEL: PL-9

MATERIAL: Extruded bronze & machined brass

12V VOLTAGE:

WATTAGE: 35 Watt

SOCKET: GY 6.35 Bi-pin porcelain socket rated 600V,

250°C 18 ga, Teflon® coated leads.

LAMPING:

T4 Halogen (order separately) 35W Maximum (order separately) 2.5W LED (order separately)

Ordering Logic:

MODEL STEM LENGTH **FINISH** METAL

PL - 9 B - Bronze 9 - 9" 12 - 12" BK - Black **BKT - Black Texture** 18 - 18" BZT - Bronze Texture BZ - Bronze

> WT - White SL - Silver BG - Beige DB - Dark Bronze

NT - Natural

ORDERING EXAMPLE: PL - 9 - B - 12 - NT

Excelsior Lighting, Inc.

PROJECT

TYPE