
Specification-grade landscape lighting, wet-location luminaire for path or garden lighting applications.

- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Seven standard TGIC powder coat finishes and clear anodized finish available.
- · Remote transformer required.
- · Stainless steel hardware.
- 6 feet of 18/2 low voltage cable supplied.
- Stems lengths of 3" 18" available. Mount not included.
- Frosted or clear tempered glass lens, glued in.
- · High-temperature silicone O-ring seals are used to seal the cap against the body.
- Molded silicone wire pass-thru is attached to socket wire prevents wicking and water leaking into the lamp compartment.
- · Listed for wet location use.
- · Warranty: 10 Years.









Specifications

MODEL: PL-6 LAMPING: T3 Halogen,

MATERIAL: Machined Aluminum 35W Maximum (order separately) 5W LED (order separately)

VOLTAGE: 12V

WATTAGE: 35 Watt

SOCKET: G4 Bi-pin porcelain socket rated 600V,

250°C 18 ga, Teflon® coated leads.

Ordering Logic:

MODEL METAL STEM LENGTH LENS STYLE OPENING SIZE FINISH

PL- 6 A - Aluminum 0 - none 9 - 9" F - Frosted 90 - 90 degrees BK- Black BKT - Black Texture 3 - 3" 12 - 12" C - Clear 120 - 120 degrees BZ - Bronze BZT- Bronze Texture

6 - 6" 18 - 18" WT - White SL - Silver

BG - Beige CA - Clear Anodized

ORDERING EXAMPLE: PL - 6 - A - 12 - F - 90 - BZT

Excelsior Lighting, Inc.

PROJECT

TYPE