


Specification-grade landscape lighting, wet-location luminaire for downlighting applications.

- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Seven standard TGIC powder coat finishes and clear anodized finish available.
- Integral LED: 2W, 4W, 6W, 9W ( 12W startup draw )
- Available in 2700K, 3000K.
- Remote magnetic transformer required.
- Not compatible with electronic transformers.
- Stainless steel hardware.
- 12" 18ga. Teflon coated wire leads.
- Cap holds 2 lens accessories.
- Mounting hardware not supplied.
- Clear tempered glass lens, glued in.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Listed for wet location use.



## Specifications

MODEL: DL - 1L

MATERIAL: 6061-T6 Aluminum

VOLTAGE: 12V

WATTAGE: 2W, 4W, 6W, 9W

SOCKET: GY 6.35 Bi-pin porcelain socket rated 600V, 250°C, Teflon ® coated leads.

LAMPING: 9W LED Module (12W startup draw )

| Wattage | 2700K    | 3000K    |
|---------|----------|----------|
| 2W      | 165 lms. | 190 lms. |
| 4W      | 345 lms. | 360 lms. |
| 6W      | 515 lms. | 530 lms. |
| 9W      | 720 lms. | 800 lms. |

## Ordering Logic:

|         |              |                                                       |                                                                                   |
|---------|--------------|-------------------------------------------------------|-----------------------------------------------------------------------------------|
| MODEL   | METAL        | FINISH                                                |                                                                                   |
| DL - 1L | A - Aluminum | BK - Black<br>BZ - Bronze<br>WT - White<br>BG - Beige | BKT - Black Texture<br>BZT - Bronze Texture<br>SL - Silver<br>CA - Clear Anodized |

ORDERING EXAMPLE: DL - 1L - A - BK - 52\*


\*See Module sheet to select module type to be installed

Excelsior Lighting, Inc.

PROJECT

TYPE

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 12V
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field replaceable

| #  | Specifications      | Lumens  |
|----|---------------------|---------|
| 50 | 2W - 9W, 2700K, 15° | 165-720 |
| 51 | 2W - 9W, 2700K, 30° | 165-720 |
| 52 | 2W - 9W, 2700K, 45° | 165-720 |
| 60 | 2W - 9W, 2700K, 60° | 165-720 |
| 53 | 2W - 9W, 3000K, 15° | 190-800 |
| 54 | 2W - 9W, 3000K, 30° | 190-800 |
| 55 | 2W - 9W, 3000K, 45° | 190-800 |
| 61 | 2W - 9W, 3000K, 60° | 190-800 |

| Wattage | 2700K    | 3000K    |
|---------|----------|----------|
| 2W      | 165 lms. | 190 lms. |
| 4W      | 345 lms. | 360 lms. |
| 6W      | 515 lms. | 530 lms. |
| 9W      | 720 lms. | 800 lms. |

#### LENSES INCLUDED

15°



45°



30°



60°

