



Specification-grade landscape lighting, wet-location luminaire for path or garden lighting applications.

- Machined aluminum, available in seven standard TGIC powder coat finishes and clear anodized finish.
- Machined brass, available in two finishes.
- Remote transformer required.
- Stainless steel hardware.
- 6 feet of 18/2 low voltage cable supplied.
- Stems lengths of 3" - 18" available. Mount not included.
- Frosted or clear tempered glass lens, glued in.
- High-temperature silicone O-ring seals are used to seal the cap against the body.
- Molded silicone wire pass-thru is attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Listed for wet location use.
- Warranty: 10 Years.



Specifications

MODEL:	PL-21	LAMPING:	T4 Halogen, 35W Maximum (order separately) 5W LED (order separately)
MATERIAL:	Machined Aluminum or Brass		
VOLTAGE:	12V		
WATTAGE:	35 Watt		
SOCKET:	GY 6.35 Bi-pin porcelain socket rated 600V, 250°C 18 ga, Teflon® coated leads.		

Ordering Logic:

MODEL	METAL	LENS STYLE	SHADE TOP	STEM LENGTH	FINISH
PL - 21	A - Aluminum	F - Frosted	S - Standard	0 - None 9 - 9"	BK - Black BKT - Black Texture
	B - Brass	C - Clear	T - Tall	3 - 3" 12 - 12"	BZ - Bronze BZT - Bronze Texture
			D - Dome	6 - 6" 18 - 18"	WT - White SL - Silver
			C - Cone		BG - Beige CA - Clear Anodized
					NT - Natural DB - Dark Bronze

ORDERING EXAMPLE: PL - 21 - A - F - D - 12 - BZT

Excelsior Lighting, Inc.

PROJECT

TYPE