Simply Better by Design™

Model	UL-3
Lamp:	MR16 Halogen or LED
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass, Flush lens
Cap Accessories:	Holds three accessories (optional)
Mounting:	1/2” NPS (order mount separately)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	10” 18 ga Teflon Coated
Weight:	.10 lbs.
Warranty:	10 Years
Dimensions:	2 3/8” dia. x 4 3/8” long

Shown in Bronze Powder Coat Finish (BZ)

SORAA DAUER BRILLIANCE

Made in USA

METALS:

6061-T6 Aluminum

Mounting Stake Options:

MT-1 MT-2 MT-6 MT-7 MT-8

ORDERING LOGIC:

Model:	UL - 3	
Metal:	A - Aluminum	
Finish:	BK - Black	BKT - Black Texture
	BZ - Bronze	BZT - Bronze Texture
	WT - White	SL - Silver
	BG - Beige	CA - Clear Anodized

ORDERING EXAMPLE: UL - 3 - A - BK

FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our ‘Flush Lens’ feature is standard on our Model UL-3. Caps drain water even when aimed straight up.

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.

SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.