

Model	WA-5L
Lamp:	LED Module: 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K. CRI = 85
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Cap Accessories:	Holds two accessories (optional)
Mounting:	Three plate options
Socket:	GY 6.35 Bi-Pin Porcelain
Certification:	Wet location, IP Rating = 66
Wiring:	10" 18 ga Teflon Coated
Weight:	1.9 lbs.
Warranty:	10 Years



Shown in Bronze Texture Powder Coat Finish (BZT)



2W/4W/6W/9W



METALS:

6061-T6 Aluminum



Mounting Plate Options:



4/0 Round



4/0 Square



3/0 Round

ORDERING LOGIC:

Model:	WA - 5L
Metal:	A - Aluminum
Mounting Plate:	1 - 4/0 Round 3 - 3/0 Round
Finish:	BK - Black BZ - Bronze WT - White BG - Beige
	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

ORDERING EXAMPLE: WA - 5L - A - 1 - BK - 52*

*See Module sheet to select module type to be installed

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 12VAC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



45°



30°



60°

