

Model	IN-5L
Lamp:	LED Module: 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K. CRI = 85
Material:	Cast Bronze frame & grate; Aluminum Lamp holder
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	18 Degrees
	Hot-Aim Feature available
Lens:	Tempered Clear Glass, Flush lens
Accessories:	Holds two accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY 6.35 Bi-pin porcelain
Certification:	Wet location, IP Rating = 67
Wiring:	6' 16/2 low voltage cable
Weight:	11.4 lbs.
Warranty:	25 Years
Dimensions:	7 1/2" square x 11 1/4" high



'Hot-Aim' Adjusting Screw

Shown in Black Powder Coat Finish (BK)



2W/4W/6W/9W

METALS:

Cast Bronze



ORDERING LOGIC:

Model:	IN - 5L	
Metal:	B - Bronze	
Aiming:	S - Standard	H - Hot Aim
Fixture Regress:	1 - 1 3/4" 3 - 4 1/4" (hot-aim)	2 - 3" (standard)
Finish:	BK - Black BZ - Bronze WT - White BG - Beige DB - Dark Bronze	BKT - Black Texture BZT - Bronze Texture SL - Silver NT - Natural

ORDERING EXAMPLE: IN - 5L - B - H - 1 - BK - 52*

*See Module sheet to select module type to be installed



HOT-AIM FEATURE:


Our 'hot-aiming' device is an important feature of our Model IN-5L Well Light. This aiming feature allows the lampholder to be adjusted vertically from straight up to 18 degrees from vertical by simply adjusting the socket head screw mounted onto the well light grate. When a project requires many well lights, this feature is an important option you will want to use.



SELECT-A-FIT:

Exclusively from Excelsior Lighting, our Xset feature allows you to set your own fixture location within our Models IN4L and IN5L well lights. This feature helps provide the proper fixture location for your lamp beam spread. Spot lamps can be located deeper into the fixture while wide floods can be located closer to the fixture grate. Our simple design offers three grooved locations on the outside of the fixture cap, one inch apart. Simply decide which setting is best for your application and snap the fixture into place!

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 12VAC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



45°



30°



60°

