

Model:	F-3
LED Module:	Adjustable 2W - 9W
	Adjustable 3W - 12W
Input Voltage:	12V AC/DC (remote transformer required)
Material:	Cast Brass
Hardware:	Stainless Steel
Finish:	Aged Brass
Knuckle:	Serrated Locking
Lens:	Tempered Clear Glass
Cap Accessories:	Holds two accessories (optional)
Mounting:	1/2" NPS (order mount separately)
IP Rating:	65
Certification:	Wet location
Wiring:	8ft. 18/2 Direct Burial Cable
Weight:	2.5 lbs.
Warranty:	10 Years
Dimensions:	2 1/4" dia. x 4 3/4" overall
	2 3/4" dia x 5 1/2" overall



METALS:

Cast Brass



Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

Wattage	2700K	3000K
3W	240 lms.	285 lms.
6W	480 lms.	570 lms.
9W	720 lms.	855 lms.
12W	960 lms.	1165 lms.

ORDERING LOGIC:

Model:	F - 3
Metal:	B - Brass
Wattage:	0 - None 2 - 2W - 9W (190 - 800 lms) 3 - 3W - 12W (210 - 1100 lms)
Kelvin:	0 - None 27 - 2700K 30 - 3000K
Beam:	0 - None 15 - 15° 30 - 30° 45 - 45° 60 - 60°

Mounting Stake Options:




SELF-CLEANING CAP:



To reduce the amount of debris that builds up on the fixture lens, our 'Self-Cleaning Lens' feature is standard on our Model F-3. Caps drain water even when aimed straight up.

ORDERING EXAMPLE: F - 3 - B - 2 - 27 - 15

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (110-780 Lumens)



- Equivalent to MR16 10W/20W/35W Halogen (equivalent CBCP)
- 2700K or 3000K
- 10.8-13.2V
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



30°



12W MULTI-LEVEL - 3W, 6W, 9W, 12W (210-1100 Lumens)



- True equivalent to MR16 20W/35W/50W Halogen (equivalent CBCP)
- 2700K or 3000K
- Equivalent to either 50W, 35W or 20W halogen light output levels
- 10.8-13.2V
- 15W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free

Wattage	2700K	3000K
3W	240 lms.	285 lms.
6W	480 lms.	570 lms.
9W	720 lms.	855 lms.
12W	960 lms.	1165 lms.

45°



60°

