

|                  |                                                  |
|------------------|--------------------------------------------------|
| Model            | ST-2L                                            |
| Lamp:            | LED Module: 2W - 9W Adjustable                   |
| Maximum Wattage: | 12W Startup draw                                 |
| Input Voltage:   | 12V (remote magnetic transformer required)       |
| Kelvin:          | 2700K, 3000K, 4000K. CRI = 85                    |
| Material:        | Machined Aluminum or Brass                       |
| Hardware:        | Stainless Steel                                  |
| Finishes:        | Seven Polyester Powder Coat, 2 Brass             |
| Lens:            | Tempered Crystalline Spread                      |
| Mounting:        | Core Drill - 2 3/8" diameter body                |
| Socket:          | GY-6.35 Bi-Pin Porcelain                         |
| IP Rating:       | 66                                               |
| Certification:   | Wet location landscape, UL2108                   |
| Wiring:          | 6' - 16/2 Low Voltage Cable                      |
| Weight:          | Aluminum: 3.0 lbs.                               |
| Warranty:        | Aluminum: 10 Years, Brass: 25 Years              |
| Dimensions:      | 3" x 5"x 3/8" thick faceplate, 6" overall length |



Shown in Bronze Powder Coat Finish (BZ)



2W/4W/6W/9W



## METALS:

6061-T6 Aluminum

Brass



## CORE DRILL DESIGN:

Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with combustible surfaces. Six feet of low voltage cable with strain relief is supplied.

## ORDERING LOGIC:

|         |                                                                       |                                                                                                      |
|---------|-----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| Model:  | ST - 2L                                                               |                                                                                                      |
| Metal:  | A - Aluminum                                                          | B - Brass                                                                                            |
| Finish: | BK - Black<br>BZ - Bronze<br>WT - White<br>BG - Beige<br>NT - Natural | BKT - Black Texture<br>BZT - Bronze Texture<br>SL - Silver<br>CA - Clear Anodized<br>DB - Dark Brass |

**ORDERING EXAMPLE:** ST - 2L - A - BK - 55\*

\*See Module sheet to select module type to be installed.



## ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:


1. Machine 6061-T6 copper-free aluminum.
2. Black anodized pre-treatment applied.
3. Polyester powder coat finish applied.



## SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

| #  | Specifications      | Lumens  |
|----|---------------------|---------|
| 50 | 2W - 9W, 2700K, 15° | 165-720 |
| 51 | 2W - 9W, 2700K, 30° | 165-720 |
| 52 | 2W - 9W, 2700K, 45° | 165-720 |
| 60 | 2W - 9W, 2700K, 60° | 165-720 |
| 53 | 2W - 9W, 3000K, 15° | 190-800 |
| 54 | 2W - 9W, 3000K, 30° | 190-800 |
| 55 | 2W - 9W, 3000K, 45° | 190-800 |
| 61 | 2W - 9W, 3000K, 60° | 190-800 |
| 62 | 2W - 9W, 4000K, 15° | 210-860 |
| 63 | 2W - 9W, 4000K, 30° | 210-860 |
| 64 | 2W - 9W, 4000K, 45° | 210-860 |
| 65 | 2W - 9W, 4000K, 60° | 210-860 |

| Wattage | 2700k    | 3000K    | 4000K   |
|---------|----------|----------|---------|
| 2W      | 165 lms  | 190 lms  | 210 lms |
| 4W      | 345 lms. | 360 lms. | 385 lms |
| 6W      | 515 lms. | 530 lms. | 590 lms |
| 9W      | 720 lms. | 800 lms. | 860 lms |

#### LENSES INCLUDED

15°



45°



30°



60°

