


Specification-grade landscape lighting, wet-location luminaire for step lighting or path lighting applications.

- Machined aluminum, available in seven standard TGIC powder coat finishes and clear anodized finish.
- Machined brass available in two finishes.
- Remote transformer required.
- Stainless steel hardware.
- Clear lens.
- Single gang junction box design.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Listed for wet location use.
- Warranty: 10 Years, Brass 25 years



Specifications

MODEL:	ST-11L	LAMPING:	1 COB LED (2W/4W) (160 lms./ 320 lms.)
MATERIAL:	Aluminum or Brass		
VOLTAGE:	12VDC		
WATTAGE:	2 Watt, 4 Watt		

Ordering Logic:

MODEL	METAL	WATTAGE	KELVIN	FINISH	
ST - 11L	A - Aluminum	2 - 2 Watt	27 - 2700K	BK - Black	BKT - Black Texture
	B - Brass	4 - 4 Watt	30 - 3000K 40 - 4000K	BZ - Bronze WT - White BG - Beige NT - Natural	BZT - Bronze Texture SL - Silver CA - Clear Anodized DB - Dark Brass

ORDERING EXAMPLE: ST - 11L - A - 2 - 27 - BK

Excelsior Lighting, Inc.

PROJECT

TYPE