

Model	PL-30L
Lamp:	Integral LED Module
Maximum Wattage:	2 watt
Input Voltage:	12VAC/DC (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	7 Polyester Powder Coat
Knuckle:	Tapered & Positive Locking, 180°
Lens:	Clear tempered borosilicate Lens
Mounting:	1/2" NPS (order mount separately)
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 18/2 low voltage cable
Weight:	1.5 lbs./4.5 lbs.
Warranty:	10 Years
Dimensions:	5 1/2" W x 2 1/2" dia.



Shown in Bronze Powder Coat Finish (BZ)



METALS:

6061-T6 Aluminum



Mounting Stake Options:



OPTIONAL GLARE SHIELD:

The PL-30L Model is available with a glare shield option.

ORDERING LOGIC:

Model:	PL - 30L	
Option:	0 - None	G - Glare Shield
Kelvin:	27 - 2700K	30 - 3000K
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

ORDERING EXAMPLE: PL - 30L - A - G - 27 - BK



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.