

Model	PL-20L
Lamp:	Integral LED: 3W, 6W, 9W, 12W
Maximum Wattage:	12 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Cover: Aluminum, Brass or Copper
Hardware:	Stainless Steel
Finishes:	Natural or Dark Bronze 7 Polyester powder coat
Lens:	Frosted Acrylic
Mounting:	SS Spike or PVC Post
Heights:	9", 12", 18"
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 18/2 low voltage cable
Weight:	8 lbs.
Warranty:	10 Years
Dimensions:	3" dia. housing



METALS:

COVER: Aluminum, Brass or Copper

INTERNAL FIXTURE: Powder coated aluminum



Aluminum



Brass



Natural Copper/
Brass Finish

Mounting Options:

PVC Stake



SS Spike



Surface Mount




ORDERING LOGIC:

Model:	PL - 20L	
Cover Metal:	A - Aluminum C - Copper	B - Brass
Optics:	1 - 180°	2 - 360°
Kelvin:	27 - 2700K	30 - 3000K
Height:	9 - 9" 12 - 12"	18 - 18"
Mounting Base:	1 - PVC Stake 3 - Surface Mount	2 - SS Spike
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized DB - Dark Bronze

Optics



180°



360°

ORDERING EXAMPLE: PL - 20L - B - 1 - 27 - 18 - 1 - DB

MULTI-LEVEL - 3W, 6W, 9W, 12W (210-1100 Lumens)



- True equivalent to MR16 20W/35W/50W Halogen (equivalent CBCP)
- 2700K or 3000K
- Replicates either 50W, 35W or 20W halogen light output levels
- 10.8-13.2V
- 15W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Dimmable to 5% with standard low-voltage phase dimmers
- Compatible with low-voltage magnetic & electronic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free