# MODEL RL-2 12V 50W MR16 8W LED

# RL-2

*Simply Better by Design™*

| Model | RL-2 |
|---|---|
| Lamp: | MR16 Halogen (order separately) |
| Maximum Wattage: | 50 watt, 8 watt LED |
| Input Voltage: | 12V (remote transformer required) |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Lens: | Frosted Acrylic Liner/Clear Glass Lens |
| Mounting: | Brass 1 inch loop |
| Socket: | GY-6.35 Bi Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location |
| Wiring: | 12” - 18 ga Shrink Tube Covered, black |
| Weight: | 1.5 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 2 3/8” dia. x 9” overall |

Shown in Bronze Texture Powder Coat Finish (BZT)

SORAA

ELI

BRILLIANCE

Made in USA

## METALS:

6061-T6 Aluminum

Optional Frosted Lens at Bottom

Frosted Acrylic Liner is Standard

## STAINLESS STEEL CABLE:

We can provide 1/16” stainless steel cable with hardware if you like. Select from various lengths from 5’-30’, in five foot increments. Contact factory for more information.

## ORDERING LOGIC:

| | | | |
|---|---|---|---|
| Model: | RL - 2 | | |
| Metal: | A - Aluminum | | |
| Bottom Lens: | 0 - None<br>1 - Frosted lens glued in | | |
| SS Cable: | 0 - None<br>5 - 5 ft<br>10 - 10 ft | 15 - 15 ft<br>20 - 20 ft<br>25 - 25 ft | 30 - 30 ft |
| 18½ Wire: | 0 - None<br>5 - 5 ft<br>10 - 10 ft | 15 - 15 ft<br>20 - 20 ft<br>25 - 25 ft | 30 - 30 ft |
| Finish: | BK - Black<br>BZ - Bronze<br>WT - White<br>BG - Beige | BKT - Black Texture<br>BZT - Bronze Texture<br>SL - Silver<br>CA - Clear Anodized | |

## ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.

## SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.

## ORDERING EXAMPLE: RL - 2 - A - 1 - 0 - 0 - BK