

Model	IN-6L
Lamp:	LED Module : 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K. CRI = 85
Material:	Cast bronze top & housing
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	20 degrees (vertical) 360 degrees (rotational)
	Hot-aim feature is standard
Lens:	Tempered Clear Glass lens
IP Rating:	68
Certification:	Wet location
Wiring:	6' 12/2 Low Voltage Cable
Weight:	8 lbs.
Warranty:	25 Years
Dimensions:	6" dia. x 4" high



Shown in Black Powder Coat Finish (BK)



2W/4W/6W/9W



METALS:

Cast Bronze



FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model IN-6L.

ORDERING LOGIC:

Model:	IN - 6L
Metal:	B - Cast Bronze
Accessory:	0 - None AH - Accessory Holder
Pour Collar:	0 - None PC - Pour Collar
Wire Entry:	1 - 6 ft 12/2 Cable 2 - Single Conduit 3 - Dual Conduit
Finish:	BK - Black BKT - Black Texture BZ - Bronze BZT - Bronze Texture WT - White SL - Silver BG - Beige NT - Natural DB - Dark Bronze



HOT-AIM FEATURE:

Our Hot-Aim feature is standard on the IN-6. This aiming feature allows the lampholder to be adjusted vertically from straight up to 18° by simply using the tool supplied.

ORDERING EXAMPLE: IN - 6L - B - 0 - PC - 1 - NT - 52*

*See Module sheet to select module type to be installed

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 12VAC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



45°



30°



60°

