

Model	MT-47
Voltage:	120V, 230V or 277V input/ 11.6V out
Wattage:	60W Dimmable
Material:	Machined Aluminum riser and cap
Mount:	1/2" NPS Thread
PVC Stake:	Available in 12" or 18"
Adjustable Riser:	9", 12", 18", 24", 30" or 36"
Fixed Sleeve Length:	8" high
Hardware:	Stainless Steel
Cap Finishes:	7 Polyester Powder Coat
Certification:	Wet location landscape, UL1838
Weight:	1.5 lbs.
Warranty:	Aluminum: 10 Years
Dimensions:	2 3/4" dia. cap, 2 3/8" dia. stake 1 3/4" dia. sleeve, 1" dia. riser



Shown in Bronze Powder Coat Finish (BZ)



METALS:

6061-T6 Aluminum Cap



ORDERING LOGIC:

Model:	MT - 47	
Metal:	A - Aluminum	B - Brass
Stake Length:	12 - 12" (standard)	18 - 18"
Riser Length:	9 - 9" 18 - 18" 30 - 30"	12 - 12" 24 - 24" 36 - 36"
Input Voltage:	120 - 120V 277 - 277V	230 - 230V
Cap Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

INTEGRAL ELECTRONIC TRANSFORMER:

For installations requiring 12V fixtures within a line-voltage system. The electronic transformer is integral within the stake mount below the fixture. Output of 11.6 volts.



1. Model TR - 6 (B+L)
 - 11.6V output
 - 120, 230, or 277 VAC input
 - 60W load maximum
 - No minimum load
 - Dimmable
 - C-UL-US UL Recognized component

DESIGN FEATURES:

Design features of our Model MT-47 Adjustable Above Ground Mount offer improved performance when compared to the competition.

Our Delrin® bushing is 'T' shaped to prevent it from 'punching through' when the riser stem is adjusted and provides positive locking.



ORDERING EXAMPLE: MT - 47 - A - 12 - 9 - 120 - BK