


Model	ST- 4L
Lamp:	LED Module: 2W - 9W Adjustable
Maximum Wattage:	12W Startup draw
Input Voltage:	12V (remote magnetic transformer required)
Kelvin:	2700K, 3000K. CRI = 85
Material:	Machined Aluminum or Brass
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat, 2 Brass
Lens:	Tempered Crystalline Spread
Mounting:	Core Drill - 2 3/8" diameter body
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL2108
Wiring:	6' - 16/2 Low Voltage Cable
Weight:	Aluminum: 3.0 lbs.
Warranty:	Aluminum: 10 Years, Brass: 25 Years
Dimensions:	5 1/2" dia. faceplate, 6" overall length



Shown in Bronze Powder Coat Finish (BZ)



2W/4W/6W/9W



METALS:

6061-T6 Aluminum

Brass



CORE DRILL DESIGN:

Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with combustible surfaces. Six feet of low voltage cable with strain relief is supplied.

ORDERING LOGIC:

Model:	ST - 4L	
Metal:	A - Aluminum	B - Brass
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized DB - Dark Brass

ORDERING EXAMPLE: ST - 4L - A - BK - 55*

*See Module sheet to select module type to be installed.

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Black anodized pre-treatment applied.
3. Polyester powder coat finish applied.




SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.



9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 12V
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



45°



30°



60°

