

Model	IN-6L
Lamp:	LED Module : 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K, 4000K. CRI = 85
Material:	Cast bronze top & housing
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	20 degrees (vertical) 360 degrees (rotational) Hot-aim feature is standard
Lens:	Tempered Clear Glass lens
Socket:	GY 6.35 Bi-pin porcelain
Certification:	Wet location, IP Rating = 68
Wiring:	6' 12/2 Low Voltage Cable or 1/2" npsf (2x)
Weight:	8 lbs.
Warranty:	25 Years
Dimensions:	6" dia. x 4" high



Shown in Black Powder Coat Finish (BK)



2W/4W/6W/9W



METALS:

Cast Bronze



FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model IN-6L.

ORDERING LOGIC:

Model:	IN - 6L
Metal:	B - Cast Bronze
Accessory:	0 - None AH - Accessory Holder
Pour Collar:	0 - None PC - Pour Collar
Wire Entry:	1 - 6 ft 12/2 Cable 2 - Single Conduit (1/2" npsf) 3 - Dual Conduit (1/2" npsf)
Finish:	BK - Black BKT - Black Texture BZ - Bronze BZT - Bronze Texture WT - White SL - Silver BG - Beige NT - Natural DB - Dark Bronze



HOT-AIM FEATURE:

Our Hot-Aim feature is standard on the IN-6. This aiming feature allows the lampholder to be adjusted vertically from straight up to 18° by simply using the tool supplied.

ORDERING EXAMPLE: IN - 6L - B - 0 - PC - 1 - NT - 52*

*See Module sheet to select module type to be installed

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800
62	2W - 9W, 4000K, 15°	210-860
63	2W - 9W, 4000K, 30°	210-860
64	2W - 9W, 4000K, 45°	210-860
65	2W - 9W, 4000K, 60°	210-860

Wattage	2700k	3000K	4000K
2W	165 lms	190 lms	210 lms
4W	345 lms.	360 lms.	385 lms
6W	515 lms.	530 lms.	590 lms
9W	720 lms.	800 lms.	860 lms

LENSES INCLUDED

15°



45°



30°



60°

