

Model	UL-1
Lamp:	MR16 Halogen or LED
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass, Flush lens
Cap Accessories:	Holds Three accessories (optional)
Mounting:	1/2" NPS (order mount separately)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	10" 18 ga Teflon Coated
Weight:	.8 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 3 3/4" long



Shown in Bronze Powder Coat Finish (BZ)



SORAA DAUER BRILLIANCE



## METALS:

6061-T6 Aluminum



Mounting Stake Options:

MT-1

MT-2

MT-6

MT-7

MT-8



## ORDERING LOGIC:

Model: UL - 1

Metal: A - Aluminum

Finish: BK - Black BKT - Black Texture  
BZ - Bronze BZT - Bronze Texture  
WT - White SL - Silver  
BG - Beige CA - Clear Anodized

ORDERING EXAMPLE: UL - 1 - A - BK

## FLUSH LENS FEATURE:



To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model UL-1. Caps drain water even when aimed straight up.

## ANODIZING PROTECTION:



To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



## SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.