

Model	ST-14
Lamp:	MR16 Halogen or LED
Maximum Wattage:	20 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum or Brass
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat, 2 Brass
Lens:	Tempered Crystalline Spread
Styles:	1/2 or 3/4 eyelid
Mounting:	Core Drill 2 1/2" dia.
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	67
Certification:	Wet location landscape, UL2108
Wiring:	6' - 16/2 Low Voltage Cable
Weight:	Aluminum: 3.0 lbs.
Warranty:	Aluminum: 10 Years, Brass: 25 Years
Dimensions:	5" dia. faceplate, 5 3/8" overall length



Shown in Bronze Powder Coat Finish (BZ)



SORAA DAUER BRILLIANCE



## METALS:

6061-T6 Aluminum

Brass



## CORE DRILL DESIGN:

Core Drill design for stone, brick or concrete installations. Core size of 2 1/2" is required. Not for use with combustible surfaces. Six feet of low voltage cable with strain relief is supplied.

## ORDERING LOGIC:

Model:	ST - 14	
Metal:	A - Aluminum	B - Brass
Style:	1 - 1/2 Eyelid	2 - 3/4 Eyelid
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized DB - Dark Brass

**ORDERING EXAMPLE:** ST - 14 - A - 1 - BK

## ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



## SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

