


Model	PL-5
Lamp:	T4 Halogen or LED
Maximum Wattage:	35 watt, 5 watt LED (order separately)
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Frosted or Clear Glass
Mounting:	1/2" NPS (order mount separately)
Stem Length:	3", 6", 9", 12", 18"
Socket:	GY 6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 16/2 low voltage cable
Weight:	1.5 lbs.
Warranty:	10 Years
Dimensions:	2 1/8" dia. top, 1" dia. stem



Shown in Bronze Powder Coat Finish (BZ)



METALS:

6061-T6 Aluminum



Mounting Stake Options:

MT-45



MT-2



MT-6



MT-7



MT-8



ORDERING LOGIC:

Model:	PL - 5	
Metal:	A - Aluminum	
Stem Length:	0 - None 3 - 3" 6 - 6"	9 - 9" 12 - 12" 18 - 18"
Lens Style:	F - Frosted	C - Clear
Opening Size:	90 - 90 degrees	120 - 120 degrees
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

ORDERING EXAMPLE: PL - 5 - A - 6 - F - 90 - BK

LIGHT DISTRIBUTION:

There are two light distributions from which to choose: 90 degree or 120 degree. These are the size of the lens opening and the light distribution is 120 and 180 degrees respectively.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.