



Model	FA-7
Lamp:	MR16 Halogen or LED
Maximum Wattage:	50 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum or brass
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Knuckle:	Tapered & Positive Locking
Lens:	Tempered Clear Glass, Flush lens
Cap Accessories:	Holds Three accessories (optional)
Mounting:	1/2" NPS (order mount separately)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	2ft. 18/2 LV wire leads
Weight:	1.3 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 10"overall



Shown in Bronze Powder Coat Finish (BZ)







SORAA

DAUER

**BRILLIANCE** 







#### METALS:

6061-T6 Aluminum C36000 Brass



#### Mounting Stake Options:

MT-1 MT-2 MT-6 MT-7 MT-8

### **ORDERING LOGIC:**

Model: FA - 7

Metal: A - Aluminum B - Brass

BK - Black **BKT - Black Texture** Finish: BZ - Bronze BZT - Bronze Texture

> WT - White SL - Silver BG - Beige CA - Clear Anodized NT - Natural DB - Dark Brass

ORDERING EXAMPLE: FA - 7 - A - BK



#### FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model FA-7. Caps drain water even when aimed straight up.



## ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.



# SEALED WIRE PASS-THRU SYSTEM:



Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.