

Model	RL-1L
Lamp:	LED Module : 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K, 4000K. CRI = 85
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Cap Accessories:	Holds two accessories (optional)
Mounting:	Brass 1 inch loop
Socket:	GY 6.35 Bi-pin Porcelain
Certification:	Wet location, IP Rating: 66
Wiring:	12" 18 ga Shrink Tube Covered, black
Weight:	.10 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 5 3/4" (7 1/8") overall



Shown in Bronze Powder Coat Finish (BZ)



Shown in Bronze Texture Finish (BZT)



2W/4W/6W/9W



Made in USA



METALS:

6061-T6 Aluminum



Straight



Angled



STAINLESS STEEL CABLE:

We can provide 1/16" stainless steel cable with hardware if you like. Select from various lengths from 5'-30', in five foot increments. Contact factory for more information.

ORDERING LOGIC:

Model:	RL - 1L		
Metal:	A - Aluminum		
Cap Style:	S - Straight A - 45° Angle		
SS Cable:	0 - None 5 - 5 ft 10 - 10 ft	15 - 15 ft 20 - 20 ft 25 - 25 ft	30 - 30 ft
1½ Wire:	0 - None 5 - 5 ft 10 - 10 ft	15 - 15 ft 20 - 20 ft 25 - 25 ft	30 - 30 ft
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized	



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees.

ORDERING EXAMPLE: RL - 1L - A - S - 0 - 0 - BK

*See Module sheet to select module type to be installed

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800
62	2W - 9W, 4000K, 15°	210-860
63	2W - 9W, 4000K, 30°	210-860
64	2W - 9W, 4000K, 45°	210-860
65	2W - 9W, 4000K, 60°	210-860

Wattage	2700k	3000K	4000K
2W	165 lms	190 lms	210 lms
4W	345 lms.	360 lms.	385 lms
6W	515 lms.	530 lms.	590 lms
9W	720 lms.	800 lms.	860 lms

LENSES INCLUDED

15°



45°



30°



60°

