ACCENT LIGHT 12V MR16 50W 8W LED MODEL AL-3

Specification-grade landscape lighting, wet-location luminaire for flood or accent lighting applications.

- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Seven standard TGIC powder coat finishes and clear anodized finish available.
- Remote transformer required.
- Stainless steel hardware.
- 2ft. 18/2 LV wire leads.
- Long flush lens cap holds 3 lens accessories.
- Clear tempered glass lens, glued in.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Listed for wet location use.
- Warranty: 10 Years.



Made in USA

Specifications

MODEL:	AL-3
MATERIAL:	6061-T6 Aluminum
VOLTAGE:	12V
WATTAGE:	50 Watt
SOCKET:	GY-6.35 Bi-pin porcelain socket rated 600V, 250°C 18 ga, Teflon® coated leads.

LAMPING:	MR16 Halogen 50W Maximum (order separately) 8W LED (order separately)

FINISHES:

BK - Black	BKT - Black Texture
BZ - Bronze	BZT - Bronze Texture
WT - White	SL - Silver
BG - Beige	CA - Clear Anodized

Ordering Logic:

MODEL	METAL	FINISH	
AL - 3	A - Aluminum	BK - Black	BKT - Textured Black
		BZ - Bronze	BZT - Textured Bronze
		WT - White	SL - Silver
		BG - Beige	CA - Clear Anodized

ORDERING EXAMPLE: AL - 3 - A - BZT

Excelsior Lighting, Inc.

PROJECT

TYPE

2507 N. Bundy Drive Fresno, CA 93727 T - 559.346.1051 F - 559.346.1071 excelsiorlighting.com