

Model	IN-4
Lamp:	MR16 Halogen or LED
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Cast Bronze frame & grate; Aluminum lampholder
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	10 Degrees
Lens:	Tempered Clear Glass, Flush lens
Accessories:	Holds Three accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	67
Certification:	Wet location landscape, UL1838
Wiring:	6' 16/2 low voltage cable
Weight:	11.4 lbs.
Warranty:	25 Years
Dimensions:	7 1/2" square x 11 1/4" high



Shown in Natural
Bronze Finish (NT)



SORAA



DAUER



BRILLIANCE



METALS:

Cast Bronze



AIMING FEATURE:

Our aiming device is an important feature of our Model IN-4 Well Light. This aiming feature allows the lampholder to be adjusted vertically from up to 10° from vertical by simply adjusting the hinged bracket attached to the well light grate. Remove the lamp housing from the bracket to change the lamp without losing the aiming of the fixture.

ORDERING LOGIC:

Model:	IN - 4
Metal:	B - Bronze
Fixture Regress:	1 - 1 3/4" 2 - 3" (standard)
Finish:	BK - Black BKT - Black Texture BZ - Bronze BZT - Bronze Texture WT - White SL - Silver BG - Beige DB - Dark Bronze NT - Natural

ORDERING EXAMPLE: IN - 4 - B - 1 - NT



SELECT-A-FIT:

Exclusively from Excelsior Lighting, our Xset feature allows you to set your own fixture location within our Models IN4 and IN5 well lights. This feature helps provide the proper fixture location for your lamp beam spread. Spot lamps can be located deeper into the fixture while wide floods can be located closer to the fixture grate. Our simple design offers three grooved locations on the outside of the fixture cap, one inch apart. Simply decide which setting is best for your application and snap the fixture into place!