

Model	PL-23
Lamp:	MR8 Halogen (order separately)
Maximum Wattage:	20 watt, 3 watt LED (order separately)
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum, brass or copper
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat, two Brass
Lens:	Tempered Clear Glass
Mounting:	1/2" NPS (order mount separately)
Stem Length:	6", 9", 12", 18", 24", 30", 36"
Socket:	GY 6.35 Bi-Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 18/2 low voltage cable
Weight:	Aluminum: 1.6 lbs. Brass/Copper: 6.5 lbs.
Warranty:	Aluminum: 10 Years Brass/Copper: 25 Years
Dimensions:	6 3/4" dia. shade, 1" dia. stem



Shown in Bronze Powder Coat Finish (BZ)



Brass

Copper



BRILLIANCE



ELI



METALS:

6061-T6 Aluminum

30333 Brass

Copper



ORDERING LOGIC:

Model:	PL - 23		
Metal:	A - Aluminum	B - Brass	C - Copper Shade
Shade Top:	S - Standard D - Dome	T - Tall C - Cone	
Stem Length:	0 - None 6 - 6" 9 - 9" 12 - 12"	18 - 18" 24 - 24" 30 - 30" 36 - 36"	
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized DB - Dark Bronze	

ORDERING EXAMPLE: PL - 23 - A - D - 12 - BZT

FEATURES:

The Model PL-23 path light is designed for lighting applications where a path light is needed with minimal glare (ie. a sloped drive or walkway.)

The light source is an MR8 lamp providing up lighting into the reflector shade, rather than a bi-pin capsule lamp that creates a point of light.



Shade Top Styles



Standard - S



Tall - T



D - Dome



C - Cone

Mounting Stake Options:

MT-45



MT-2



MT-6



MT-7



MT-8

