


Specification-grade landscape lighting, wet-location luminaire for up lighting or down lighting applications. Can be utilized for ground mounted or surface mounted installations.

- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Seven standard TGIC powder coat finishes and clear anodized finish available.
- Stainless steel hardware.
- 10" 18ga. Teflon coated wire leads.
- Medium base ceramic socket
- 1" regressed lens cap holds 1 lens accessory.
- Mount not included.
- Clear tempered glass lens, glued in.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Listed for wet location use.
- Warranty: 10 Years.



Specifications

MODEL:	DL - 29	LAMPING:	PAR20 Halogen, 50W Maximum (order separately) 11W LED (order separately)	
MATERIAL:	6061-T6 Aluminum			
VOLTAGE:	120VAC			
WATTAGE:	50 Watt	FINISHES:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized
SOCKET:	Medium base ceramic socket rated 600V, 250°C 18 ga, Teflon® coated leads.			

Ordering Logic:

MODEL	METAL	MOUNTING PLATE	STEM LENGTH		FINISH	
DL - 29	A - Aluminum	1 - MT-24	0 - None	9 - 9"	BK - Black	BKT - Black Texture
		2 - MT-25	3 - 3"	12 - 12"	BZ - Bronze	BZT - Bronze Texture
		3 - MT-26	6 - 6"	18 - 18"	WT - White	SL - Silver
		4 - MT-27			BG - Beige	CA - Clear Anodized

ORDERING EXAMPLE: DL - 29 - A - 1 - 0 - BK

Excelsior Lighting, Inc.

PROJECT:

TYPE: