

Simply Better by Design™

Model	MT-3
Voltage:	120V, 230V or 277V input/ 11.6V out
Wattage:	60W Dimmable
Material:	Machined Aluminum Cap
Mount:	1/2" NPS Thread
PVC Stake:	Available in 12" or 18"
Hardware:	Stainless Steel
Cap Finishes:	7 Polyester Powder Coat
Weight:	1.5 lbs.
Certification:	Wet location landscape, UL1838.
Warranty:	Aluminum: 10 Years
Dimensions:	2 3/4" dia. cap, 2 3/8" dia. stake



Shown in Bronze Powder Coat Finish (BZ)





METALS:

6061-T6 Aluminum Cap



ORDERING LOGIC:

Model: MT - 3

Metal: A - Aluminum B - Brass

Stake Length: 12 - 12" (standard) 18 - 18"

Style: 1 - 60W, dimmable

Input Voltage: 120 - 120V 230 - 230V

277 - 277V

Cap Finish: BK - Black BKT - Black Texture

BZ - Bronze BZT - Bronze Texture

WT - White SL - Silver

BG - Beige CA - Clear Anodized NT - Natural DB - Dark Bronze

ORDERING EXAMPLE: MT - 3 - A - 12 - 1 - 120- BK

INTEGRAL ELECTRONIC TRANSFORMER:

For installations requiring 12V fixtures within a line-voltage system. The electronic transformer is integral within the stake mount below the fixture. Output of 11.6 volts.



- 1. Model TR 6 (B+L)
 - 11.6V output
 - 120, 230, or 277 VAC input
 - 60W load maximum
 - No minumum load
 - Dimmable
 - · C-UL-US UL Recognized component

DESIGN FEATURE:

An important design feature of our Model MT-3 Mount offers improved performance when compared to the competition.

Instead of using three, very small 6-32 size allen screws, we use 10-32 size. They are located 1/2" from the base of the mounting cap to keep it out of the soil thereby reducing the chance of corrosion, being filled with dirt and stripping the hardware during maintenance.

