

Model	PL-24
Lamp:	MR8/MR11 Halogen
Maximum Wattage:	20 watt, 3 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Cap:	Three cap styles available
Mounting:	Adjustable or fixed
Stem Length:	9", 12", 18", 24", 30", 36"
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	6 ft. 18/2 low voltage cable
Weight:	2.4 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 5 1/4" long



Shown in Bronze Powder Coat Finish (BZ)



ELI (MR8)



ELI (MR11)



BRILLIANCE

METALS:

6061-T6 Aluminum



Mounting Stake Options:

MT-45

MT-2

MT-6

MT-7

MT-8



ORDERING LOGIC:

Model:	PL - 24
Metal:	A - Aluminum
Cap:	1 - Flush 2 - Regress 3 - 45 Degree
Stem Length:	9 - 9" 12 - 12" 18 - 18" 24 - 24" 30 - 30" 36 - 36"
Finish:	BK - Black BZ - Bronze WT - White BG - Beige BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.