

Model	PL-14L
Lamp:	Integral LED: 2W, 4W, 6W, 9W (12W Startup Draw)
Maximum Wattage:	9 watt LED (dual)
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Cap:	Three cap styles available
Mounting:	1/2" NPS (order mount separately)
Stem Length:	9", 12", 18", 24", 30", 36" (vertical)
Socket:	GY 6.35 Bi-Pin Porcelain
Certification:	Wet location, IP Rating = 66
Wiring:	6 ft. 18/2 low voltage cable
Weight:	4.2 lbs.
Warranty:	10 Years
Dimensions:	7" luminaire, 1" dia. stem



Shown in Bronze Powder Coat Finish (BZ) with 9" fixture spacing



2W/4W/6W/9W



METALS:

6061-T6 Aluminum



Mounting Stake Options:



ORDERING LOGIC:

Model:	PL - 14L	
Metal:	A - Aluminum	
Cap:	1 - Flush 3 - 45 Degree	2 - Regress
Fixture Spacing:	9 - 9" 11 - 11"	13 - 13" 19 - 19"
Vertical Stem Length:	9 - 9" 12 - 12" 18 - 18"	24 - 24" 30 - 30" 36 - 36"
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

ORDERING EXAMPLE: PL - 14L - A - 1 - 9 - 24 - BK - 52*

*See Module sheet to select module type to be installed

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:


1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-800 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K or 3000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable

#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800

Wattage	2700K	3000K
2W	165 lms.	190 lms.
4W	345 lms.	360 lms.
6W	515 lms.	530 lms.
9W	720 lms.	800 lms.

LENSES INCLUDED

15°



45°



30°



60°

