

| | |
|------------------|--|
| Model | PL-31 |
| Lamp: | T4 Halogen or LED |
| Maximum Wattage: | 20 watt, 3 watt LED (order separately) |
| Input Voltage: | 12V (remote transformer required) |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Lens: | Tempered Frosted Glass |
| Mounting: | Core Drill - 1 3/8" diameter body |
| Options: | 1, 2 or 4 openings |
| Socket: | GY 6.35 Bi Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location landscape, UL1838 |
| Wiring: | 6 ft. 16/2 low voltage cable |
| Weight: | 1.5 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 3" dia. x 3" overall |



Shown in Bronze Powder Coat Finish (BZ)



METALS:

6061-T6 Aluminum



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.

ORDERING LOGIC:

| | | |
|-----------|---|---|
| Model: | PL - 31 | |
| Metal: | A - Aluminum | |
| Openings: | 1 - Single 2 - 2 @ 180° 4 - 4 @ 90° | |
| Finish: | BK - Black BZ - Bronze WT - White BG - Beige | BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized |



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

ORDERING EXAMPLE: PL - 31 - A - 1 - BK