

Model	PL-20L
Lamp:	LED Module: 2W - 12W Adjustable
Maximum Wattage:	15W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K
Material:	Machined Aluminum, Brass or Copper Cover
Hardware:	Stainless Steel
Finishes:	Seven Polyester powder coat
Lens:	Frosted Acrylic
Mounting:	SS Spike or PVC Post
Heights:	9", 12", 18"
Socket:	GY 6.35 Bi-Pin Porcelain
Certification:	Wet location, IP Rating = 66
Wiring:	6 ft. 18/2 low voltage cable
Weight:	8 lbs.
Warranty:	10 Years
Dimensions:	3" dia. housing



METALS:

COVER: Aluminum, Brass or Copper

INTERNAL FIXTURE: Powder coated aluminum



Aluminum



Brass



Natural Copper/
Brass Finish

Mounting Options:

PVC Stake



SS Spike



Surface Mount




ORDERING LOGIC:

Model:	PL - 20L	
Cover Metal:	A - Aluminum C - Copper	B - Brass
Optics:	1 - 180°	2 - 360°
Kelvin:	27 - 2700K	30 - 3000K
Height:	9 - 9" 12 - 12"	18 - 18"
Mounting Base:	1 - PVC Stake 3 - Surface Mount	2 - SS Spike
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized DB - Dark Bronze

Optics




180°



360°

ORDERING EXAMPLE: PL - 20L - B - 1 - 27 - 18 - 1 - NT

12W MULTI-LEVEL - 2W, 4W, 6W, 9W, 12W (210-1165 Lumens)



- True equivalent to MR16 20W/35W/50W Halogen (equivalent CBCP)
- 2700K or 3000K
- Equivalent to either 50W, 35W or 20W halogen light output levels
- 12VAC/DC
- G5.3 bi-pin base
- 15W startup draw
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field replaceable

Wattage	2700K	3000K
2W	210 lms.	230 lms.
4W	340 lms.	385 lms.
6W	580 lms.	670 lms.
9W	820 lms.	915 lms.
12W	960 lms.	1165 lms.



2W / 4W / 6W / 9W / 12W

External 5 positions switch to change the wattage manually.