STAFF LIGHT 12V 10W INTEGRAL LED MODEL PL-7L

Specification-grade landscape lighting, wet-location luminaire for path or garden lighting applications.

- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Seven standard TGIC powder coat finishes and clear anodized finish available.
- Integral LED Module: 4W, 7W, 10W.
- Available in 2700K, 3000K.
- Remote transformer required.
- Stainless steel hardware.
- 6 feet of 18/2 low voltage cable supplied.
- Three cap styles from which to choose.
- Stems lengths of 9”- 36” available.
- Adjustable or fixed mounting. (see MT-1 and MT-2)
- Clear tempered glass lens, glued in.
- High-temperature silicone O-ring seals are used to seal the cap against the body.
- Molded silicone wire pass-thru is attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Listed for wet location use.
- Warranty: 10 Years.





90° Flush



90°Regress

Made in USA

Specifications:

MODEL:	PL-7L	LAMPING:	10W Integral LED Module
MATERIAL:	6061-T6 Aluminum		
VOLTAGE:	10.8-13.2V		
WATTAGE:	4W, 7W, 10W		

Ordering Logic:

MODEL	METAL	CAP	STEM LENGTH		FINISH	
PL - 7L	A - Aluminum	1 - Flush	9 - 9”	24 - 24”	BK - Black	BKT - Black Texture
		2 - Regress	12 - 12”	30 - 30”	BZ - Bronze	BZT - Bronze Texture
		3 - 45 Degree	18 - 18”	36 - 36”	WT - White	SL - Silver
					BG - Beige	CA - Clear Anodized

ORDERING EXAMPLE: PL - 7L - A - 1 - 12 - BZT - 52*

*See Terralux Module sheet to select module type to be installed

Excelsior Lighting, Inc.

PROJECT

TYPE

2507 N. Bundy Drive Fresno, CA 93727 T - 559.346.1051 F - 559.346.1071 excelsiorlighting.com

MR16 INTEGRAL MODULES

Simply Better by Design™

MULTI-LEVEL - 4W, 7W, 10W

- True equivalent to MR16 20W/35W/50W Halogen (equivalent CBCP)
- Replicates either 50W, 35W or 20W halogen light output levels
- 10.8-13.2V
- 15W startup draw
- Interchangeable lenses: 12°, 25°, 40°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Dimmable to 5% with standard low-voltage phase dimmers
- Compatible with low-voltage magnetic & electronic transformers
- L70=60,000 hours
- 5 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Compatible with B+L Model EX95101 electronic transformer (order separately)
- Compatible with Lutron dimmer models:
  - Diva DELV-300/303P
  - Maestro MAELV-600
  - Skylark SELV 300PH

NO.	Specifications	Lumens
50	4W/7W/10W, 2700K, 12°	342/494/635
51	4W/7W/10W, 2700K, 25°	342/494/635
52	4W/7W/10W, 2700K, 40°	342/494/635
53	4W/7W/10W, 3000K, 12°	351/533/705
54	4W/7W/10W, 3000K, 25°	351/533/705
55	4W/7W/10W, 3000K, 40°	351/533/705