

Model	PL-6
Lamp:	T4 Halogen or LED (order separately)
Maximum Wattage:	35 watt, 5 watt LED (order separately)
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Frosted or Clear Glass
Mounting:	1/2" NPS (order mount separately)
Stem Length:	3", 6", 9", 12", 18"
Socket:	GY 6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	6 ft. 18/2 low voltage cable
Weight:	1.5 lbs.
Warranty:	10 Years
Dimensions:	2 1/8" dia. top, 1" dia. stem



Shown in Bronze Powder Coat Finish (BZ)



METALS:

6061-T6 Aluminum

Mounting Stake Options:



ORDERING LOGIC:

Model:	PL - 6
Metal:	A - Aluminum
Stem Length:	0 - None 9 - 9" 3 - 3" 12 - 12" 6 - 6" 18 - 18"
Lens Style:	F - Frosted C - Clear
Opening Size:	90 - 90° 180 - 180° 120 - 120°
Finish:	BK - Black BKT - Black Texture BZ - Bronze BZT - Bronze Texture WT - White SL - Silver BG - Beige CA - Clear Anodized

ORDERING EXAMPLE: PL - 6 - A - 6 - F - 90 - BK

LIGHT DISTRIBUTION:

There are three light distributions from which to choose: 90°, 120° or 180°. These are the sizes of the lens opening and the light distribution is 120 and 180 degrees respectively.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:



1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.