

Model	IN-2
Lamp:	MR16 Halogen (order separately)
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass lens
Accessories:	Holds Three accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	67
Certification:	Wet location
Wiring:	6' 16/2 Low Voltage Cable
Weight:	2.5 lbs.
Warranty:	10 Years
Dimensions:	3" dia. x 7" overall (5 1/2" tall housing)



Shown in Bronze Powder Coat Finish (BZ)



SORAA



ELI



BRILLIANCE



METALS:

6061-T6 Aluminum



FLUSH LENS FEATURE:



To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model IN-2. Caps drain water even when aimed straight up.

ORDERING LOGIC:

Model:	IN - 2	
Metal:	A - Aluminum	
Cutoff Height:	S - Short (1")	T - Tall (1 1/2")
Opening Size:	90 - 90°	180 - 180°
Pour Collar:	0 - None (standard) PC - Pour Collar (optional)	
Finish:	BK - Black BZ - Bronze WT - White BG - Beige	BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

ORDERING EXAMPLE: IN - 2 - A - T - 0 - 90 - BK



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.