

Model	RL-1
Lamp:	MR16 Halogen or LED
Maximum Wattage:	50 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass
Cap Accessories:	Holds three accessories (optional)
Mounting:	Brass 1 inch loop
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	12" 18 ga Shrink Tube Covered, black
Weight:	.10 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 4 3/4" (6 1/8") overall



Shown in Bronze Powder Coat Finish (BZ)



Shown in Bronze Texture Finish (BZT)



SORAA



DAUER



BRILLIANCE



Made in USA



METALS:

6061-T6 Aluminum



Straight



Angled



STAINLESS STEEL CABLE:

We can provide 1/16" stainless steel cable with hardware if you like. Select from various lengths from 5'-30', in five foot increments. Contact factory for more information.

ORDERING LOGIC:

Model:	RL - 1
Metal:	A - Aluminum
Cap Style:	S - Straight A - 45° Angle
Cable:	0 - None 5 - 5 ft 10 - 10 ft 15 - 15 ft 20 - 20 ft 25 - 25 ft 30 - 30 ft
Finish:	BK - Black BZ - Bronze WT - White BG - Beige BKT - Black Texture BZT - Bronze Texture SL - Silver CA - Clear Anodized

ORDERING EXAMPLE: RL - 1 - A - S - 0 - BK



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.